9.0 FENSTRATION PRODUCT RATING CERTIFICATE (IP)

OVERALL RATING U-factor: (Btu/h·ft²·°F) Certificate Authorization SHGC: VT: Name: Company: Signature: Date: STIPULATES THAT THE MATERIALS LISTED ON THIS CERTIFICATE WERE INSTALLED ON THE PROJECT IDENTIFIED BELOW PROJECT INFORMATION: Street Address: City: State: GLAZING CONTRACTOR / INSTALLER: Contact Person: Street Address: Phone Number: City: State: Zip: GLAZING MATERIAL SUPPLIER: Contact Person: **FABLE 1 - GLAZING** Street Address: Phone Number: City: State: Zip: # Glass and Spacer Type: Center-of-glass (C.O.G.) U-factor: Center-of-glass (C.O.G.) SHGC: Center-of-glass (C.O.G.) VT: Btu/h·ft2.°F FRAMING MATERIAL SUPPLIER: Contact Person: YKK AP America Inc David Warden Phone Number: Street Address: 101 Marietta Street NW, Suite 2700 678-838-6000 City: State: Zip 30303 Atlanta Georgia **U-factor Matrix** SHGC Matrix VT Matrix Btu/h·ft²·°F Product Line: C.O.G. Overall C.O.G. Overall C.O.G. Overall YHS 50 TU Pre-Glazed (Inside Glazed) U-factor U-factor SHGC SHGC VT VT Storefront 0.48 0.56 0.75 0.65 0.75 0.64 0.59 0.46 0.55 0.70 0.60 0.70 The overall ratings for U-factor, SHGC and VT are 0.44 0.53 0.65 0.56 0.65 0.55 based on a size of 79 in. X 79 in. as 0.42 0.60 0.52 0.60 0.51 required in NFRC 100 and NFRC 200. 0.51 0.55 0.48 0.55 0.47 0.40 0.50 0.42 0.50 0.44 0.50 0.48 Overall U-factors, Solar Heat Gain Coefficients (SHGC) and 0.38 0.45 0.38 0.39 0.45 0.36 0.47 Visible Transmittances (VT) listed in the matrix were 0.40 0.35 0.40 0.34 0.34 0.45 determined in accordance with NFRC 100 and NFRC 200 0.32 0.44 0.35 0.31 0.35 0.30 respectively by an accredited, independent laboratory. 0.30 0.42 0.30 0.27 0.30 0.25 ACCREDITED INDEPENDENT LABORATORY: 0.25 0.22 0.25 0.21 0.28 0.41 0.20 0.17 0.26 0.39 0.20 0.18 Reference NFRC 100 Report #: N4095.02-116-45-R0 0.15 Reference 507-07 Report #: 0.24 0.37 0.15 0.14 0.13 N4095.01-116-45-R0 0.10 0.10 0.10 0.08 Reference AWS Test Report #: M1416.03-550-18-R1 0.22 0.36 0.05 0.05 0.04 0.05 0.20 0.34 0.18 0.32 Air Leakage less than or equal to 0.06 cfm/ft² Directions: Fill out form completely. Determine the Overall Rating for this project by using the C.O.G. U-factor (winter-time), at a test pressure of 6.24 PSF when tested in 0.16 0.31 accordance with (check one) C.O.G. SHGC, C.O.G. VT from Table 1 and looking up the 0.29 0.14 AAMA/WDMA/CSA 101/I.S.2/A440 overall rating from Table 2. Indicate the Overall Rating in the space above. Linear interpolation is permitted. 0.12 0.28 Х ASTM E283 (6.24 PSF) 0.10 0.26 NFRC 400