

**YKK
ap**

Commercial
Standard Entrance
Hardware



Description

- Adams-Rite® series 4510 Deadlatch
- Standard backset is 1-1/8" (narrow stile door) or 1-1/2" (medium & wide stile doors).
- Assembly accepts any standard 1-5/32" diameter mortised cylinder, thumbturn cylinder, or dummy cylinder. All operating cylinder types require MS cam.
- Accepts Adams-Rite® 4560 lever handles.
- Requires a H-3303 or H-3304 faceplate and a H-3501, H-3502 or H-3503 strike.

Compatible Entrances

H-3205(RH)/H-3206(LH): (1-1/8" backset) 20D & 25T

H-3207(RH)/H-3208(LH): (1-1/2" backset) 35D/50D, 35T/50T, 40M/50M, 35XT/50XT & 35H/50H

Material Composition

Aluminum Alloy and Mill Finish

Dimensions

Case: 1" x 6" x backset depth

Bolt: 5/8" x 1-3/8" with 13/16" throw

Faceplate: 1" x 6-7/8"

Hardware Vendor



ASSA ABLOY

Vendor Part or Series

Adams Rite® MS-4510-36-201-628 (1-1/8" backset RH or LHR)

Adams Rite® MS-4510-35-201-628 (1-1/8" backset LH or RHR)

Adams Rite® MS-4510-46-201-628 (1-1/2" backset RH or LHR)

Adams Rite® MS-4510-45-201-628 (1-1/2" backset LH or RHR)

H-3205 / H-3206 & H-3207 / H-3208

Optional Standard Deadlatch Assembly