

YSD 400 SPECS							
Base Depth	4"						
Sightline	2" to 2-1/4"						
Config	Pre-Glazed or Factory Glazed / Center Set						
Tested Glass	1" Laminated IGU with Low-E (C.O.G. U-Factor: 0.29)						
Test	Test Results						
Air Infiltration	0.30 CFM/FT <sup>2</sup> (1.10 m³/h·m²) @ 6.24 PSF (299 Pa)	ASTM E 283					
Water Infiltration	Ctatic: 15 PCF (/18 Pa)						
Acoustical	Standard STC: 31 Standard OITC: 27	ASTM E 90					
(1" IGU)	Laminated STC: 33 Laminated OITC: 30	ASTM E 1425					

Thermal Performance								
Mullion Depth	U-Factor - BTU/hr·ft².°F					CRF		
2" x 4" (Normal Sill)	0.55	0.54	0.52	0.51	0.49	0.48	Not Tested	
Center of Glass	0.30	0.28	0.26	0.24	0.22	0.20	Frame	Glass
AAMA 507					AAMA	\ 1503		

Finish Options					
Туре	Standard				
Factory Anodized	AAMA 612				
Organic Paints	AAMA 2604 AAMA 2605				

Forced Entry Res	istance
Tested in accordance	
and meets the	ASTM F 842
requirements of	TAS 202
Performance Grade 10	

**NOTE:** Balcony door configuration will effect the performance specifications.

## **Configurations**














High


Head









## **Product Details**





Normal Head











## **Standard Hardware**

Our YSD 400 has Pull Handles, Integral Handles, Recessed Handles, Thumbturn and Lockbolt options available.



Additional information including CAD details, CSI specs, test reports and installation instructions are found on the Product Guide by clicking this link or visiting www.ykkap.com/commercial/productguide

©2024 YKK AP America Inc. 06-5000-07